



BRUYNZEEL MULTIGROOVE



BRUYNZEEL PLYWOOD
La Motte Michel, 79270 Le Vanneau
Tel. : +33 (0)5 49 35 15 82
contact.bruynzeel@groupe-arbor.com
www.bruynzeel-plywood.com



FACES	Peeled Okoume veneers 13/10 ^{ths} Faces quality A/BB*
INNER LAYERS	Thin & Selected & Garant plies - 100% Okoume
GLUE	Class 3 - Outdoor use Glue Standard EN 314
DIMENSIONAL TOLERANCE	Standard EN 315
DENSITY	500 kg/m ³ (+/- 10%). Standard EN 323



E1



The mark of responsible forestry

RECOMMENDED APPLICATIONS



Cladding



Garage door



Roof soffits & edges



Outdoor ceiling

BENEFITS

Perfect timber plank cladding effect
 Excellent mechanical resistance
 Highly resistant to moisture
 Naturally durable ■ Thin plies
 Rigorously selected veneers

*ADDITIONAL INFORMATION: Face 1 Interlocking tongue & grooves. Spacing : 111 mm - Depth : 4,2 mm - Width : 10 mm

DIMENSIONS (MM)		THICKNESS (MM)	
		9	15
2500 x 1242	No. of plies	5	7
	Pack size*	Minimum 32, then multiple of 16	Minimum 16, then multiple of 16

* quantity per pack may vary within the scope of +/-10%