



BRUYNZEEL PAINTPANEL



BRUYNZEEL PLYWOOD
 La Motte Michel, 79270 Le Vanneau
 Tel.: +33 (0)5 49 35 15 82
 contact.bruynzeel@groupe-arbor.com
 www.bruynzeel-plywood.com



FACES	Peeled Okoume veneers 10/10 ^{ths} Faces quality B/B with white phenolic film
INNER LAYERS	Selected plies - 100% Okoume
GLUE	Class 3 - Outdoor use Glue Standard EN 314
DIMENSIONAL TOLERANCE	Standard EN 315
DENSITY	500 kg/m ³ (+/- 10%). Standard EN 323



E1

CE



The mark of responsible forestry

RECOMMENDED APPLICATIONS

- Caravans, RVs
- Commercial vehicles, Vans
- Cladding
- Garage door
- Roof soffits & edges
- Indoor & outdoor joinery
- Indoor & outdoor furniture
- Indoor wall & ceiling
- Outdoor ceiling

BENEFITS

Ready to paint white phenolic film on both sides

- Excellent mechanical resistance
- Highly resistant to moisture
- Naturally durable
- Time saving
- Rigorously selected veneers

DIMENSIONS (MM)		THICKNESS (MM)			
		10	12	15	18
2500 x 1220	No. of plies	5	7	7	9
	Pack size*	50	40	30	25

* quantity per pack may vary within the scope of +/-10%